

CAPELLA GEN2 VAPOR PROOF



CCT	3000K / 4000K / 5000K / 6500K
CRI	80
SDCM	3
UGR	<24
Beam Angle	124'
IP Rating	IP66
LED Lumen Depreciation	L80B10 @ 74000Hrs
Driver Lifetime Specification	F10 – 100000Hrs
Surge Protection	2Kva
Ripple	<5%
Diffuser Material	UV Stabilized Polycarbonate
Housing	Injected polycarbonate, with UV protection Grey RAL 7035
Gasket	Polyurethane
Clips	Stainless Steel
Operating Temperature	-30 – 45°C
Warranty	5 Years

MODIFICATION	WATTAGE	EFFICIENCY	LUMEN PACKAGE
2Ft 250Ma	13W	130 Lumen / W	1690 Lumens
2Ft 350Ma	17W	125 Lumen / W	2125 Lumens
2Ft 450Ma	23W	118 Lumen / W	2714 Lumens
4Ft 250Ma	25W	130 Lumen / W	3183 Lumens
4Ft 350Ma	34W	125 Lumen / W	4160 Lumens
4Ft 450Ma	45W	118 Lumen / W	5281 Lumens
5Ft 250Ma	32W	130 Lumen / W	4160 Lumens
5Ft 350Ma	43W	125 Lumen / W	5375 Lumens
5Ft 450Ma	54W	118 Lumen / W	6372 Lumens
5Ft 500Ma	64W	119 Lumen / W	7645 Lumens