

SINEALUX



Dimensions	50mm x 50mm
CCT	3000 / 4000 / 5000 / 6500 K
CRI	80
SDCM	3
Beam Angles	30° / 60° / 90° / 110° / High Rack / DBL ASYM / ASYM
IP Rating	IP20
LED Lumen Depreciation	L80 B10 @ 93 000 Hrs
Driver Lifetime Specification	F10 - 100000Hrs
Dimming Options	DALI
Surge Protection	4kV (Option 10/20kV inline)
Housing Material	Extruded Aluminum – Rust Resistant Powder Coating
Housing Colours	Black / White / Custom RAL
Ripple	5%
Linkable	Yes
Optic Material	PMMA
Operational Temperature	-25°C - 40°C
Total Warranty	7 Year Warranty

VARIATION	LENGTH	WATTAGE	EFFICIENCY	LUMENS
ESS 4	1200mm	18W	135 Lumens / W	2499 Lumens
ESS 4	1200mm	24W	133 Lumens / W	3095 Lumens
ESS 4	1200mm	34W	127 Lumens / W	4250 Lumens
ESS 4	1200mm	49W	120 Lumens / W	5906 Lumens
ESS 4	1200mm	60W	116 Lumens / W	6982 Lumens
ESS 4	1500mm	42W	120 Lumens / W	7383 Lumens
ESS 4	1500mm	74W	116 Lumens / W	8729 Lumens
ADV 6	1200mm	57W	129 Lumens / W	7381 Lumens
ADV 6	1500mm	71W	127 Lumens / W	9226 Lumens
ADV 6	1700mm	100W	127 Lumens / W	12917 Lumens
ADV 6	2000mm	115W	127 Lumens / W	14762 Lumens